

PLCC Series

5630 Robin W HE

Datasheet




Ceiling Light


Down Light


Wide Angle Lamp


Panel Light


Tube Light

Introduction :

Edison PLCC 5630 Robin W series features uniform light distribution, excellent light quality and wide angle design (150°x125°). Besides, the small package of 5630R White series can be used with optical lens for wide angle applications such as bulb, down light and street light.

Description :

- Industry standard compatible 5.6mmx3.0mm package
- High efficiency 166 lm per watt at 4000K
- Optical lens for wide angle design (150°x125°)

Feature and Benefits :

- High luminous Intensity and high efficiency
- Based on Blue : InGaN technology
- ANSI Compliant color binning
- Suitable for all SMT assembly methods
- IR reflow process compatible
- Environmental friendly; RoHS compliance



Table of Contents



General Information

Ordering Code Format

2	T	0 5	X 5	x W	x x	0 0 0	x x x
X1	X2	X3-X4	X5-X6	X7-X8	X9-X10	X11-X13	X14-X16

X1 Type		X2 Component		X3-X4 Series		X5-X6 Wattage		X7-X8 Color	
2	Emitter	T	PLCC	05	5630	X5	0.5W	CW	Cool White
								NW	Neutral White
								WW	Warm White

X9-X10 Internal code		X11-X13 PCB Board		X14-X16 Serial Number	
-	-	000	-	-	-



Absolute Maximum Ratings (Ta=25°C)

Parameter	Symbol	Value	Units
Forward Current	I_F	200	mA
Pulse Forward Current (tp<=100μs, Duty cycle=0.25)	I_{pulse}	350	mA
Reverse Current	I_R	10	uA
Reverse Voltage	V_R	[2]	V
LED Junction Temperature	T_J	125	°C
Operating Temperature	-	-40 ~ +85	°C
Storage Temperature	-	-40 ~ +125	°C
ESD Sensitivity (HBM)	V_B	2,000	V
Soldering Temperature	T_s	Reflow Soldering : 255~260°C/10~30sec Manual Soldering : 350°C/3sec	

Notes:
1. Proper current derating must be observed to maintain junction temperature below the maximum at all time.
2. LEDs are not designed to be driven in reverse bias.

Characteristics

Parameter	Symbol	Value	Units
Viewing Angle (Typ.)	$2\Theta_{1/2}$	150x125	Degree
Thermal resistance	-	20	°C/W
CRI	-	>80	-
CCT (Cool White) (Neutral White) (Warm White)	-	2,700 3,000 3,500 4,000 5,000 5,700 6,500	K
JEDEC Moisture Sensitivity	-	Level 2a **Floor Life** Conditions: ≤30˚C / 60% RH **Soak Requirements(Standard)** Time (hours): 120+1/-0 Conditions: 60˚C / 60% RH	-

Notes:
1. $2\theta_{1/2}$ is the off-axis angle where the luminous intensity is half of the axial luminous intensity.
2. Color Rendering index CRI tolerance: ±2.
3. CIE_x/y tolerance: ±0.005



Electro - Optical Characteristics (Neutral White)

I_F=65mA and T_J=25˚C

If (mA)	Vf (V)	Power (W)	lm	lm/W
30	2.73	0.082	14.8	180.5
60	2.85	0.171	28.7	167.8
65(typ.)	2.86	0.186	31.0	166.6
90	2.96	0.266	41.9	157.5
120	3.06	0.367	54.3	147.9
150	3.17	0.476	66.1	138.9
180	3.25	0.585	77.3	132.1
200	3.31	0.662	84.5	127.6

Note:
LM Values are for representative reference only.



Luminous Flux Characteristic

Luminous Flux Characteristics, I_F=65mA and T_J=25˚C

Color	Group	Min. Luminous Flux(lm)	Max. Luminous Flux(lm)	Forward Current (mA)	Order Code
Cool White	28	28	30	65	2T05X5CW11000017
	30	30	32		
	32	32	34		
Neutral White	28	28	30		2T05X5NW11000017
	30	30	32		
	32	32	34		
Warm White	26	26	28		2T05X5WW11000017
	28	28	30		
	30	30	32		

Note:
The luminous flux performance is guaranteed within published operating conditions. Edison Opto maintains a tolerance of ±10% on flux measurements.

Voltage Bin Structure


Group	Min. Voltage (V)	Max. Voltage (V)
VC0	2.7	2.8
VA1	2.8	2.9
VB1	2.9	3.0
VC1	3.0	3.1

Note:
Forward voltage measurement allowance is ± 0.06V.




Mechanical Dimensions


Emitter Type Dimension



Circuit



Solder Pad



Notes:
1. All dimensions are measured in mm.
2. Tolerance : ± 0.20 mm




Color BIN code

Color region stay within Macadam "3-Step/5-step" ellipse from the chromaticity center.
The chromaticity center refers to ANSI C78.377:2008.
Please refer to ANSI C78.377 for the chromaticity center.

CCT	Steps	Cx	Cy	a	b	theta
2700K	5	0.4578	0.4101	0.01350	0.00700	53.70
3000K	5	0.4338	0.4030	0.01390	0.00680	53.22
3500K	5	0.4073	0.3917	0.01545	0.00690	54.00
4000K	5	0.3818	0.3797	0.01565	0.00670	53.72
5000K	5	0.3447	0.3553	0.01370	0.00590	59.62
5700K	5	0.3287	0.3417	0.01243	0.00533	59.09
6500K	5	0.3123	0.3282	0.01115	0.00475	58.57


CCT	Steps	Cx	Cy	a	b	theta
2700K	3	0.4578	0.4101	0.00810	0.00420	53.70
3000K	3	0.4338	0.4030	0.00834	0.00408	53.22
3500K	3	0.4073	0.3917	0.00927	0.00414	54.00
4000K	3	0.3818	0.3797	0.00939	0.00402	53.72
5000K	3	0.3447	0.3553	0.00822	0.00354	59.62
5700K	3	0.3287	0.3417	0.00746	0.00320	59.09
6500K	3	0.3123	0.3282	0.00669	0.00285	58.57

Cool White






Neutral White



Warm White





6500K

65X		65B		65A		65W	
X	Y	X	Y	X	Y	X	Y
0.3005	0.3415	0.3115	0.3391	0.3130	0.3290	0.3068	0.3113
0.3099	0.3509	0.3028	0.3304	0.3048	0.3207	0.3144	0.3186
0.3115	0.3391	0.3048	0.3207	0.3068	0.3113	0.3161	0.3059
0.3028	0.3304	0.3130	0.3290	0.3144	0.3186	0.3093	0.2993

65Y		65C		65D		65Z	
X	Y	X	Y	X	Y	X	Y
0.3099	0.3509	0.3205	0.3481	0.3213	0.3373	0.3144	0.3186
0.3196	0.3602	0.3115	0.3391	0.3130	0.3290	0.3221	0.3261
0.3205	0.3481	0.3130	0.3290	0.3144	0.3186	0.3231	0.3120
0.3115	0.3391	0.3213	0.3373	0.3221	0.3261	0.3161	0.3059

5700K

57X		57B		57A		57W	
X	Y	X	Y	X	Y	X	Y
0.3196	0.3602	0.3290	0.3538	0.3290	0.3417	0.3222	0.3243
0.3290	0.3690	0.3207	0.3462	0.3215	0.3350	0.3290	0.3300
0.3290	0.3538	0.3215	0.3350	0.3222	0.3243	0.3290	0.3180
0.3207	0.3462	0.3290	0.3417	0.3290	0.3300	0.3231	0.3120

57Y		57C		57D		57Z	
X	Y	X	Y	X	Y	X	Y
0.3290	0.3690	0.3376	0.3616	0.3371	0.3490	0.3290	0.3300
0.3381	0.3762	0.3290	0.3538	0.3290	0.3417	0.3366	0.3369
0.3376	0.3616	0.3290	0.3417	0.3290	0.3300	0.3361	0.3245
0.3290	0.3538	0.3371	0.3490	0.3366	0.3369	0.3290	0.3180

5000K

50X		50B		50A		50W	
X	Y	X	Y	X	Y	X	Y
0.3381	0.3762	0.3463	0.3687	0.3451	0.3554	0.3366	0.3369
0.3480	0.3840	0.3376	0.3616	0.3371	0.3490	0.3440	0.3427
0.3463	0.3687	0.3371	0.3490	0.3366	0.3369	0.3429	0.3307
0.3376	0.3616	0.3451	0.3554	0.3440	0.3427	0.3361	0.3245

50Y		50C		50D		50Z	
X	Y	X	Y	X	Y	X	Y
0.3480	0.3840	0.3551	0.3760	0.3533	0.3620	0.3440	0.3427
0.3571	0.3907	0.3463	0.3687	0.3451	0.3554	0.3515	0.3487
0.3551	0.3760	0.3451	0.3554	0.3440	0.3427	0.3495	0.3339
0.3463	0.3687	0.3533	0.3620	0.3515	0.3487	0.3429	0.3307



4000K

40X		40B		40A		40W	
X	Y	X	Y	X	Y	X	Y
0.3771	0.4034	0.3871	0.3959	0.3828	0.3803	0.3670	0.3578
0.3736	0.3874	0.3736	0.3874	0.3702	0.3722	0.3640	0.3440
0.3871	0.3959	0.3702	0.3722	0.3670	0.3578	0.3740	0.3491
0.3914	0.4115	0.3828	0.3803	0.3784	0.3647	0.3784	0.3647

40Y		40C		40D		40Z	
X	Y	X	Y	X	Y	X	Y
0.3914	0.4115	0.4006	0.4044	0.3950	0.3875	0.3784	0.3647
0.3871	0.3959	0.3871	0.3959	0.3828	0.3803	0.3740	0.3491
0.4006	0.4044	0.3828	0.3803	0.3784	0.3647	0.3844	0.3552
0.4060	0.4208	0.3950	0.3875	0.3898	0.3716	0.3898	0.3716

3500K

35A		35B		35C		35D	
X	Y	X	Y	X	Y	X	Y
0.4083	0.3921	0.4148	0.4090	0.4299	0.4165	0.4223	0.399
0.3941	0.3848	0.3996	0.4015	0.4148	0.4090	0.4083	0.3921
0.3889	0.3690	0.3941	0.3848	0.4083	0.3921	0.4018	0.3752
0.4018	0.3752	0.4083	0.3921	0.4223	0.399	0.4147	0.3814

3000K

30A		30B		30C		30D	
X	Y	X	Y	X	Y	X	Y
0.4345	0.4033	0.4431	0.4213	0.4562	0.4260	0.4468	0.4077
0.4223	0.3990	0.4299	0.4165	0.4431	0.4213	0.4345	0.4033
0.4147	0.3814	0.4223	0.3990	0.4345	0.4033	0.4260	0.3854
0.4260	0.3854	0.4345	0.4033	0.4468	0.4077	0.4373	0.3893


2700K

27A		27B		27C		27D	
X	Y	X	Y	X	Y	X	Y
0.4578	0.4101	0.4687	0.4289	0.4813	0.4319	0.4703	0.4132
0.4468	0.4077	0.4562	0.4260	0.4687	0.4289	0.4578	0.4101
0.4373	0.3893	0.4468	0.4077	0.4578	0.4101	0.4483	0.3919
0.4483	0.3919	0.4578	0.4101	0.4703	0.4132	0.4593	0.3944




Characteristic curve

Color Spectrum




Beam Pattern






Forward Current vs. Forward Voltage




Relative Luminous Intensity vs. Forward Current






Relative Luminous Flux vs. Junction Temperature




Forward Voltage vs. Junction Temperature






Δx,Δy vs. Forward Current




Δx,Δy vs. Junction Temperature






Maximum Current vs. Ambient Temperature





Reflow Profile

The following reflow profile is from IPC/JEDEC J-STD-020D which provided here for reference.



Reflow Profiles

Classification Reflow Profiles

Profile Feature	Pb-Free Assembly
Preheat & Soak Temperature min (Tsmin) Temperature max (Tsmax) Time (Tsmin to Tsmax) (ts)	150 °C 200 °C 60-120 seconds
Average ramp-up rate (Tsmax to Tp)	3 °C/second max.
Liquidous temperature (TL) Time at liquidous (tL)	217 °C 60-150 seconds
Peak package body temperature (Tp)*	255 °C ~260 °C *
Classification temperature (Tc)	260 °C
Time (tp)** within 5 °C of the specified classification temperature (Tc)	30** seconds
Average ramp-down rate (Tp to Tsmax)	6°C/second max.
Time 25°C to peak temperature	8 minutes max.

Notes:
1. * Tolerance for peak profile temperature (Tp) is defined as a supplier minimum and a user maximum.
2. ** Tolerance for time at peak profile temperature (tp) is defined as a supplier minimum and a user maximum.



Reliability


NO .	Test Item	Test Condition	Remark
1	Temperature Cycle	-40°C~100°C 30, 30, mins	100 Cycle
2	Thermal Shock	-40°C~100°C 15, 15 mins ≦10 sec	100 Cycle
3	Resistance to Soldering Heat	T_{SOL}=260°C, 30 sec	3 times
4	Moisture Resistance	25°C~65°C 90% RH 24 hrs / 1 cycle	10 Cycle
5	High-Temperature Storage	T_A=100°C	1,000 hrs
6	Humidity Heat Storage	T_A=85°C RH=85%	1,000 hrs
7	Low-Temperature Storage	T_A=-40°C	1,000 hrs
8	Operation Life test	25°C	1,000 hrs
9	High Temperature Operation Life test	85°C	1,000 hrs
10	High Humidity Heat Life Test	85°C, 85%RH	1,000 hrs
11	ON/OFF Test	30 sec ON, 30 sec OFF	1.5W times

Failure Criteria

Item	Criteria for Judgment	
	Min.	Max.
Lumen Maintenance	85%	-
Δu'v'	-	0.006
Forward Voltage	-	Initial Data x 1.1
Reverse Current	-	10 μA
Resistance to Soldering Heat	No dead lamps or visual damage	




Reliability



Test Item	Specification (mm)
W	12.00
E	1.75
F	5.50
D0	1.50
D1	1.50
P0	4.00
P1	8.00
P2	2.00
t	0.25
A0	3.45
B0	5.90
K0	2.40

Reel Specification





Revision History

Versions	Description	Release Date
1	Establish a Datasheet	2015/07/23

About Edison Opto

Edison Opto is a leading manufacturer of high power LED and a solution provider experienced in LDMS. LDMS is an integrated program derived from the four essential technologies in LED lighting applications- Thermal Management, Electrical Scheme, Mechanical Refinement, Optical Optimization, to provide customer with various LED components and modules. More Information about the company and our products can be found at www.edison-opto.com

www.edison-opto.com

For general assistance please contact:
service@edison-opto.com.tw

For technical assistance please contact:
LED.Detective@edison-opto.com.tw